

SOFAR 15-25KTLX-G3P

15 / 17 / 20 / 23 / 25 kW

THREE-PHASE DUAL MPPT



Product advantages

- Compatible with 182 & 210 high power PV modules
- Low start-up voltage, wide MPPT voltage range
- Prolonged AC overload compatibility (110%)
- Type II SPD for both DC and AC side
- Remote firmware upgrade



Model	SOFAR 15KTLX-G3P	SOFAR 17KTLX-G3P	SOFAR 20KTLX2-G3P	SOFAR 23KTLX-G3P	SOFAR 25KTLX-G3P
Input (DC)					
Max. input voltage	1100V				
Rated input voltage	620V				
Start-up voltage	180V				
MPPT operating voltage range	160-1000V				
Number of MPP trackers	2				
Number of DC inputs	1/2		2/2		
Max. input MPPT current	20A/32A		40A/32A		
Max. input short circuit current	25A/40A		50A/40A		
Output (AC)					
Rated output power	15000W	17000W	20000W	23000W	25000W
Max. apparent power	16500VA	18700VA	22000VA	25300VA	27500VA
Max. output current	25.1A	28.5A	33.5A	38.5A	41.8A
Rated output voltage	3/N/PE, 220/380Vac, 230/400Vac, 240/415Vac				
Output voltage range	310-480Vac				
Rated output frequency	50/60Hz				
Output frequency range	45-55Hz/55-65Hz				
Active power adjustable range	0-100%				
THDi	<3%				
Power factor	0.8 leading – 0.8 lagging				
Efficiency					
Max. efficiency	≥98.6%				
European efficiency	≥98.1%				
Protection					
DC reverse polarity protection	Yes				
Anti-islanding protection	Yes				
Leakage current protection	Yes				
Ground fault monitoring	Yes				
PV-array string fault monitoring	Yes				
DC switch	Yes				
SPD	PV: type II, AC: type II				
General Data					
Ambient temperature range	-30°C to +60°C				
Self-consumption at night	<1W				
Topology	Transformerless				
Degree of protection	IP66				
Allowable relative humidity range	0-100%				
Max. operating altitude	4000m (> 2000m derating)				
Cooling	Smart air cooling				
Dimension (W×H×D)	491×412×188mm				
Weight	19kg	20kg	20.5kg		
Display	LCD & Bluetooth +APP				
Communication	RS485/Wi-Fi				
Standard	IEC/EN 62109-1/2, IEC/EN 61000-6-1/2/3/4, IEC 62116, IEC 61727, IEC 61683, IEC 60068-2-1/2/14/30, PORTARIA INMETRO N° 140, ABNT NBR 16149/16150				

*All specifications are subject to change without notice.